

Protego[®] Plus HT and HTX Purifiers

APPLICATIONS

Cartridges

- Bulk DI water applications
- Point-of tool purification

Disposables

- Point-of-use
- Lab scale

FEATURES & BENEFITS

sample09




SPECIFICATIONS


Materials	Membrane	7 nm: Hydrophilic polysulfone
		1 nm: Non dewetting polysulfone
	Ion exchange media	Polyethylene
	Supports, core, sleeve, end caps	Polypropylene
	O-rings	Encapsulated fluoropolymer (E-FKM) or Kalrez® 6375 UP
	Chemlock® Key	Polypropylene
Connections	Cartridges	Code 0 (2-222 O-rings)
		Code 7 (2-226 O-rings/spear) for 30" HT
Operating conditions	Maximum inlet pressure	0.34 MPa (3.4 bar, 50 psi) @ 25°C (77°F)
	Maximum forward differential pressure	0.27 MPa (2.7 bar, 40 psid) @ 25°C (77°F)
		0.05 MPa (0.5 bar, 7 psid) @ 80°C (176°F)
	Maximum reverse differential pressure	0.27 MPa (2.7 bar, 40 psid) @ 25°C (77°F)
	Maximum operating temperature	80°C (176°F) at the above conditions
Membrane surface area	10" cartridge	HT: 0.52 m² (5.60 ft²)
		HTX: 0.93 m² (10.01 ft²)
	20" cartridge	HT: 1.04 m² (11.19 ft²)
		HTX: 1.67 m² (17.98ft²)
	30" cartridge	HT: 1.56 m² (16.79 ft²)
Ion exchange capacity	10" cartridge	HT: ≥74 meq/unit
		HTX: ≥110 meq/unit
	20" cartridge	HT: ≥148 meq/unit
		HTX: ≥220 meq/unit
	30" cartridge	HT: ≥222 meq/unit

PERFORMANCE DATA


Protego Plus HTX 10" Purifier




Protego Plus HTX 10" Filters




Protego Plus HTX 20" Filters




Protego Plus HT 10" Filters



Protego Plus HT 20" Filters




Protego Plus HT 30" Filters




DRAWINGS

Code 0 – End View with Chemlock Key on Cartridge




HTX 10" and 20" Cartridges

Code 0 – with Chemlock Key




HT 10" and 20" Cartridges

Code 0 – with Chemlock Key



HT 30" Cartridge

Code 7



ORDERING INFORMATION

PART NUMBER	RETENTION RATING	CONNECTION	LENGTH	O-RING	CHEMLOCK® KEY	PURIFICATION CAPACITY
PRH001PLQ	Ion exchange media only	Code 0	10"	E-FKM	No	74 meq/unit
PRH001PLQY	Ion exchange media only	Code 0	10"	E-FKM	Yes	74 meq/unit
PRH001PQ1	Ion exchange media only	Code 0	10"	E-FKM	No	110 meq/unit
PRH001PQ1Y	Ion exchange media only	Code 0	10"	E-FKM	Yes	110 meq/unit
PRH002PLQ	Ion exchange media only	Code 0	20"	E-FKM	No	148 meq/unit
PRH002PLQY	Ion exchange media only	Code 0	20"	E-FKM	Yes	148 meq/unit
PRH002PQ1	Ion exchange media only	Code 0	20"	E-FKM	No	220 meq/unit
PRH002PQ1Y	Ion exchange media only	Code 0	20"	E-FKM	Yes	220 meq/unit
PRHE01PPR0T	1 nm	Code 0	10"	Perfrez® PXC Ultra	No	110 meq/unit
PRHE01PPRYT	1 nm	Code 0	10"	Perfrez® PXC Ultra	Yes	110 meq/unit
PRHE01PQ10T	1 nm	Code 0	10"	E-FKM	No	110 meq/unit
PRHE01PQ1YT	1 nm	Code 0	10"	E-FKM	Yes	110 meq/unit
PRHM01PQ1	7 nm	Code 0	10"	E-FKM	No	110 meq/unit
PRHM01PQ1Y	7 nm	Code 0	10"	E-FKM	Yes	110 meq/unit
PRHM01PR1	7 nm	Code 0	10"	Kalrez® 6375	No	110 meq/unit

FOR MORE INFORMATION

Please call your Regional Customer Service Center today to learn what Entegris can do for you. Visit entegris.com and select the [Contact Us](#) link to find the customer service center nearest you.

TERMS AND CONDITIONS OF SALE

All purchases are subject to Entegris' Terms and Conditions of Sale. To view and print this information, visit entegris.com and select the [Terms & Conditions](#) link in the footer.



Corporate Headquarters
129 Concord
Billerica, MA 01821
USA

Customer Service
Tel +1 952 556 4181
Fax +1 952 556 8022
Toll Free 800 394 4083

Entegris®, the Entegris Rings Design®, and other product names are trademarks of Entegris, Inc. as listed on entegris.com/trademarks. All third-party product names, logos, and company names are trademarks or registered trademarks of their respective owners. Use of them does not imply any affiliation, sponsorship, or endorsement by the trademark owner.

Entegris, Inc. | All rights reserved. | Printed in the USA | 4415--1025