

Protego® Plus IPA Purifier

APPLICATIONS

- Industry: Semiconductor (Wet Clean and Clean)
- Chemistry: Solvent
- Installation Point: Point-of-Tool

FEATURES & BENEFITS

test




SPECIFICATIONS


		Chem-Line™ II ATE 10" Disposable	P3000 Disposable	P1500 Disposable
Materials:	Membrane	PTFE		
	Supports, shell	PFA		
Purification capable:		Metal removal		
Purification capacity:		4.30 meq	1.18 meq	0.48 meq
Retention rating:		15 nm		
Fittings sizes		1/2" I/O - 1/4" V/D Super 300 Type Pillar®	1/2" I/O - 1/4" V/D Super 300 Type Pillar	1/2" I/O - 1/4" V/D Super 300 Type Pillar
		3/4" I/O - 1/4" V/D Super 300 Type Pillar	3/8" I/O - 1/4" V/D Super 300 Type Pillar	3/8" I/O - 1/4" V/D Super 300 Type Pillar
		3/4" I/O - 1/2" V/D Super 300 Type Pillar	8 mm I/O - 6mm V/D Super 300 Type Pillar	8 mm I/O - 6 mm V/D Super 300 Type Pillar
		1" I/O - 1/4" V/D Super 300 Type Pillar	8 mm I/O - 6 mm V/D Super 300 Type Pillar	8 mm I/O - 6 mm V/D Super 300 Type Pilla
		1" I/O - 1/2" V/D Super 300 Type Pillar	3/8" I/O - 1/4" V/D Flaretek	3/8" I/O - 1/4" V/D Flaretek
		3/4" I/O - 1/4" V/D Flaretek®		
		3/4" I/O - 1/2" V/D Flaretek		
		1" I/O - 1/4" V/D Flaretek		
NVR extractables:		≤1.0 mg/device (IPA)	≤0.4 mg/device (IPA)	
Metals extractables:		<3 ug/device		
Filtration area:		1.77 m ² (19.05 ft ²)	0.49 m ² (5.27 ft ²)	0.20 m ² (2.15 ft ²)
Flow resistance with 2 L/min IPA @ 1.96 cP (25°C):		11.5 kPa @ Inlet/Outlet 1"	39 kPa	99 kPa
Flow resistance with 2 L/min IPA @ 0.97 cP (about 50°C):		9.2 kPa @ Inlet/Outlet 1"	19 kPa	49 kPa
Operating conditions:	Temperature rating	70°C (158°F)		
	Maximum operating pressure	0.58 MPa @ 25°C (77°F)	0.44 MPa @ 25°C (77°F)	
	Maximum forward differential pressure	0.44 MPa @ 25°C (77°F)	0.39 MPa @ 25°C (77°F)	
	Maximum reverse differential pressure	0.34 MPa @ 25°C (77°F)	0.26 MPa @ 25°C (77°F)	

PERFORMANCE DATA


Protego Plus IPA Purifiers Small Disposable Filters




Protego Plus IPA Purifiers Chem-Line II ATE Disposable Filters – 1" Fittings




Protego Plus IPA Purifiers 10" Chem-Line II Filters ½" Fittings



Protego Plus IPA Purifiers 10" Chem-Line II Filters ¾" and 1" Fittings



Protego Plus IPA Purifiers Small Disposable P1500/P3000








DRAWINGS

Protego IPA 1500 UCM 15 nm $\frac{3}{8}$ " Super 300 Type Pillar









FOR MORE INFORMATION

Please call your Regional Customer Service Center today to learn what Entegris can do for you. Visit entegris.com and select the [Contact Us](#) link to find the customer service center nearest you.

TERMS AND CONDITIONS OF SALE

All purchases are subject to Entegris' Terms and Conditions of Sale. To view and print this information, visit entegris.com and select the [Terms & Conditions](#) link in the footer.



Corporate Headquarters
129 Concord
Billerica, MA 01821
USA

Customer Service
Tel +1 952 556 4181
Fax +1 952 556 8022
Toll Free 800 394 4083

Entegris®, the Entegris Rings Design®, and other product names are trademarks of Entegris, Inc. as listed on entegris.com/trademarks. All third-party product names, logos, and company names are trademarks or registered trademarks of their respective owners. Use of them does not imply any affiliation, sponsorship, or endorsement by the trademark owner.

Entegris, Inc. | All rights reserved. | Printed in the USA | 4447--1025

www.entegris.com